

# Sustainable Green Emollients: Plant Alkanes Replacing Volatile Silicones (Engineering Review 2015)

Por Cristiano Ricardo · Publicado em 19/10/2015

Technical dermocosmetic engineering lecture by Prof. Cristiano Ricardo on sustainable green emollients: plant alkanes replacing volatile silicones (Green Chemistry & Cosmetic Raw Material R&D), featuring colorful schematic diagrams and clinical data.

Versão online e eventuais atualizações:

<https://professor.cristianoricardo.com/post/sustainable-green-emollients-plant-alkanes-replacing-volatile-silicones-2015-10-19>

---

Green Chemistry & Cosmetic Raw Material R&D · Cosmetic Engineering & Science

Transitioning from petroleum-derived volatile cyclosiloxanes (D5, D6) to circular, bio-based hydrocarbons.

## Engineering Mechanism & Kinetic Flowchart

Cyclopentasiloxane (D5)

? Synthetic Organosilicon

? Environmental Bioaccumulation (vPvB)

Global Regulatory Restrictions

C13-15 Alkane (Hemisqualane)

? 100% Fermented Sugarcane

? Readily Biodegradable (OECD 301)

Identical Dry Sensorial Slip & Spread

## Fermentation-Derived Hemisqualane (C13-15 Alkane)

Engineered through the yeast fermentation of renewable sugarcane, this branched isoalkane replicates the low surface tension, volatility, and feather-light dry slip of D5 silicone without aquatic toxicity.

## Spreading Cascade Optimization

Blending fast-spreading polar esters with slow-spreading vegetable triglycerides establishes a continuous sensory cascade: instant spreadability on initial rub-out transitioning to long-lasting barrier comfort.

## OECD 301 Ready Biodegradability

Modern sustainable inputs must achieve > 60% mineralization into CO<sub>2</sub> and water within a 10-day window under OECD 301 guidelines, preventing persistent micro-pollutants in wastewater.

Prof. Cristiano Ricardo

Pharmacist-Biochemist · Specialist in Cosmetic Engineering & Dermato-Pharmacology ·  
Published on October 19, 2015 at 18:21